	k			几械有限公 g Machine		
				anhai District, Fos		
Helen Yao	Vebsite	186-757-88554253 Fax:0086-757		-88554252 Mobil	e: 0086-13927728664 <u>salesl@fscspack.net</u> <u>csmachine168@aliyun.com</u> <u>helen.fschuansong@aliyun.com</u>	
		QUO	TATION of F	Packing mac	hine	
Photo ITEM NO			Unit Price(USD) FOB Guangzhou	Specification		
					Model:	DCTWB-450D
				\$7,700.00	Film width:	Max.450mm
					Bag length:	130~450mm
					Bag width:	50~220mm
			DCTWB-450D (Rotary pillow Packing machine)		Product height:	Max.90mm
Fr Contraction		film roll diameter:			Max.320mm	
					Packing speed:	30~100 bags/minute
V.					power supply:	220V, 50/60Hz, 2.6Kw
					Machine weight:	900kg
5. Temperature 6. Positioned stor 7. Simple driving 8. All controls re Remark: 1. the price we of 2. Warranty: 1 y 3. Tenure of use 4. Delivery time: 5. Price availabi 6. Machine Pack 7. Payment term 3. Engineers av 9. On line techn 10. Staff training	independent PID co op function, without g system, realible w ealized through softwork offered which made rear (We provide ne e: over 15 years. : 7-15 days after real lity: within 2 months kage: plastic film + 1 ns: 30% deposit in a ailable to service ma ic service and offer g on line, or when years	bontrol, more suit sticking knife or orking, convenie ware, easy for fu by normal steel w free parts for ceiving first payr coam + wooden advance, 70% ba achinery overse solution within 2 bu visit our facto	able for packaging diffe wasting film. ent maintenance. Inction adjusting and te and parts contact with clients in a warranty pe nent. case with fumigation. alance should be paid l as. 24 hours, if any questio ry.	echnical upgrade. moterial are made by s rriod). pefore delivery.	stainless steel.	steel 304 which resist
List of attached documents, fittings and tools A. Documents 1. Machine instruction manual 2. PLC construction specification B. Fittings 1. Push block 5pieces stainless steel 2. End-sealing cutters 1 pair 3. Mid-sealing drive belt 1 piece 4. Mid-sealing electric heating tube 2 pieces 110V 200W 5. End-sealing electric heating tube 2 pieces 110V 250W				Main parts Touch Screen: Samkoo, China(Japanese technology) or Wecon invertor: Panasonic, Japan PLC: Panasonic, Japan Button: Schneider, Germany Temperature controller: Yatai, Shanghai Solid state relay: Fotek, Taiwan Middle state relay: Omron, Japan Magic eye: Baideli, Taiwan Twist Button: Schneider, Germany		

